interfering signal will not produce more than 1.0 dB degradation of the practical threshold of the microwave receiver for analog system, or such that the interfering signal will not cause an increase in the bit error rate (BER) from 10E-6 to 10E-5 for digital systems.

(g) The development of the C/I ratios and interference criteria specified in paragraphs (e) and (f) of this section and the methods employed to compute the interfering power at the microwave receivers shall follow generally acceptable good engineering practices. The procedures described for computing interfering signal levels in (Appendix I to this subpart E Appendix E of the Memorandum Opinion and Order, GEN Docket No. 90-314, FCC 94-144) shall be applied. Alternatively, procedures for determining interfering signal levels and other criteria as may be developed by the Electronics Industries Association (EIA), the Institute of Electrical and Electronics Engineers, Inc. (IEEE), the American National Standards Institute (ANSI) or any other recognized authority will be acceptable to the Commission.

[59 FR 32854, June 24, 1994, as amended at 61 FR 29691. June 21, 1996]

§24.238 Emission limits.

(a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB.

(b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licens-

ee's frequency block edges, both upper and lower, as the design permits.

- (d) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.
- (e) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

POLICIES GOVERNING MICROWAVE RELO-CATION FROM THE 1850–1990 MHZ BAND

§ 24.239 Cost-sharing requirements for broadband PCS.

Frequencies in the 1850-1990 MHz band listed in §101.147(c) of this chapter have been allocated for use by PCS. In accordance with procedures specified in §§ 101.69 through 101.81 of this chapter. PCS entities (both licensed and unlicensed) are required to relocate the existing Fixed Microwave Services (FMS) licensees in these bands if interference to the existing FMS operations would occur. All PCS entities who benefit from spectrum clearance by other PCS entities or a voluntarily relocating microwave incumbent, must contribute to such relocation costs. PCS entities may satisfy this requirement by entering into private cost-sharing agreements or agreeing to terms other than those specified in §24.243. However, PCS entities are required to reimburse other PCS entities or voluntarily relocating microwave incumbents that incur relocation costs and are not parties to the alternative agreement. In addition, parties to a private cost-sharing agreement may seek reimbursement through the clearinghouse (as discussed in §24.241) from PCS entities that are not parties to the agreement. The cost-sharing plan is in effect during all phases of microwave relocation specified in §101.69 of this chapter.

[62 FR 12757, Mar. 18, 1997]

§24.241 Administration of the Cost-Sharing Plan.

The Wireless Telecommunications Bureau, under delegated authority, will select an entity to operate as a neutral, not-for-profit clearinghouse. This clearinghouse will administer the cost-